Security Euro Cylinder Pull and Escutcheon





Features

- Stylish security cylinder pull and escutcheon For use with a Euro profile cylinder
- Designed to provide an easy method of closing the door upon exit
 Used to pull the door close from the outside easily
- Solid cylinder protection
 Design of the cylinder pull protects the external cylinder behind the pull preventing cylinder snapping and extraction
- Internal rounded escutcheon slides easily onto the fixing plate Finishes the door internally
- All parts for a door included within one package
 Supplied as a pair external cylinder pull and internal escutcheon boxed together with screws for 42-48mm doors (screw pack available for 70mm doors)
- Designed for Composite, Timber and PVCu doors
 To suit all door materials
- Available in the complete range of Hardex finishes
 Perfectly matching to the full Fab&Fix range of products
- Through fixing
 Easily retro-fittable and suitable for all locking mechanisms. Screw centres perfectly align with key wind up, Heritage and Slam Shut door locking systems
 - Secure
 High tensile M6 screws for high security performance. Meets the requirements of PAS24 as part of a compliant doorset and tested to meet TS007













EXTERNAL DOORS

Security Euro Cylinder Pull and Escutcheon

Ordering Details 83mm Security Euro Cylinder Pull and Escutcheon

Finish	Part No. 42-48mm doors
Hardex Chrome	4F152
Hardex Bronze	4F153
Hardex Gold	4F154
Hardex Graphite	4F155
Hardex Rose	DFNSEPEHR
Antique Black	4F156
White	4F150
Black	4F151
Screw pack for 70mm doors	9F102

	60.00
38 00	

52.00

Technical Information		
Corrosion resistance Meets the requirements of BS EN 1670:2007 Grade 5 (480 hours)		
Material Specification		
Cylinder Pull:	High quality Zinc	
Escutcheon:	High quality Zinc	
Coatings:	Hardex Chrome, Hardex Bronze, Hardex Gold, Hardex Graphite, Hardex Rose, Antique Black, Black and White	

Maintenance

For continued protection of the quality finish and appearance, we advise routine cleaning of all our external hardware. We recommend wiping it with a clean cloth soaked in warm water and mild detergent every month. Please refrain from using heavy-duty cleaners, containing Chlorine or Potassium. Moving parts should also be lightly lubricated using a light non-acidic mineral oil (e.g., "3 in 1") at least twice per year. The product may need to be adjusted and fixings tightened to ensure a satisfactory operation. This procedure is particularly essential if products are used within a 25-mile radius of coastal areas or close proximity to building sites or large industrial areas, where more frequent cleaning may be required to prevent the accumulation of corrosive contaminants.



Security Euro Cylinder Pull and Escutcheon Individually boxed with screws.

20 per box.

All dimensions are in mm and are nominal. Fab&Fix reserves the right to change specification without notice It is the responsibility of the door manufacturer to ensure that the finished product meets any required safety and performance specification.



